

# SPECIFICATIONS - bizhub 958 / 758

## bizhub 958/758 General Specifications

		bizhub 958	bizhub 758
Type		Console	
Copy	Scan	Main: 600dpi x Sub: 600dpi	
	Print	1,200 dpi x 1,200 dpi	
Gradation		256	
Memory size		4 GB	
HDD		250 GB	
Original Type		Sheets, Books, Objects	
Max. Original Size		A3 (11" x 17")	
Output Size		Main unit: SRA3*, A3 to A5, 12-1/4" x 18" (A3 wide (311.1 mm x 457.2 mm)), 12" x 18" (A3 wide (304.8 mm x 457.2 mm)), 11" x 17" to 8-1/2" x 11", 5-1/2" x 8-1/2", 8" x 13** <sup>2</sup> , 16K** <sup>3</sup> , 8K, Postcard Bypass Tray: SRA3, A3 to A5, B6** <sup>4</sup> , A6** <sup>4</sup> , 12" x 18" (A3 wide (304.8 mm x 457.2 mm)), 11" x 17" to 5-1/2" x 8-1/2", 8" x 13" ** <sup>5</sup> , 16K, 8K, Postcard (A6 (4" x 6" Card)), Envelope** <sup>6</sup> , Index paper, Banner paper (Width: 210 mm to 297 mm (8-1/4" to 11-11/16"), Length: 457 mm to 1,200 mm (18" to 47-1/4"))** <sup>7</sup>	
Image Loss		Max. 4.2mm or less for top edge (5 mm for thin paper), Max. 3.0mm or less for bottom edge, Max. 3.0mm or less for right/left edges *A loss of 4.2 mm each during printing.	
Warm-Up Time** (23 C, std. voltage)		55 sec. or less	22 sec. or less
	*The time required to start printing when both the main power and sub-power switches are turned from OFF to ON.	55 sec. or less	22 sec. or less
	*The time required to start printing when the main power switch is ON and the sub-power switch is turned from OFF to ON.	55 sec. or less	22 sec. or less
First Copy Out Time**		3.2 sec. or less	3.6 sec. or less
Copy Speed (A4)		95 ppm	75 ppm
Copy Magnification	Fixed Same Magnification	1: 1 0.5% or less	
	Scaling Up	1: 1.154/1.224/1.414/2.000	
	Scaling Down	1: 0.866/0.816/0.707/0.500	
	Preset	3 types	
	Zoom	25 to 400% (in 0.1% increments)	
	Lengthwise Crosswise Individual Settings	25 to 400% (in 0.1% increments)	
Paper Capacity	Tray 1 / Tray 2	500 sheets (up to SRA3)	
	Tray 3	1,500 sheets (up to A4)	
	Tray 4	1,000 sheets (up to A4)	
	Bypass Tray	150 sheets (up to SRA3)	
	Max. Paper Capacity (80 g/m <sup>2</sup> ) *10	6,650 sheets	
Paper Weight	Main Unit	52 to 256 g/m <sup>2</sup>	
	Multiple BypassTray	52 to 300 g/m <sup>2</sup>	
Multiple Copy		1 to 9,999 sheets	
Auto Duplex	Paper Size	SRA3, A3 to A5, B6** <sup>4</sup> , A6** <sup>4</sup> , 12-1/4" x 18" (A3 wide (311.1 mm x 457.2 mm)), 12" x 18" (A3 wide (304.8 mm x 457.2 mm)), 11" x 17" to 5-1/2" x 8-1/2", 7-1/4" x 10-1/2", 8" x 13", 16K, 8K, Postcard (A6 (4" x 6" Card))	
	Paper Weight	52 to 256 g/m <sup>2</sup>	
Power Requirements		AC220 to 240 V 10 A (50/60 Hz)	
Max. Power Consumption		3.6 kW or less	2.1 kW or less
Dimensions [W] x [D] x [H]		670 x 820 x 1,232 mm (26-3/8" x 32-5/16" x 48-1/2") *Main unit + ADF	
Weight		Approx. 200 kg (440-15/16 lb)	
Space Requirements [W] x [D]**1		1,008 x 1,419 mm (39-11/16" x 55-7/8")	

- \*1 SRA3 paper can be used in Tray2.  
 \*2 There are four types of fooscap: 8-1/2" x 13-1/2"  8-1/2" x 13"  8-1/4" x 13"  and 8" x 13" . Any one of these sizes is selectable. For details, contact your service representative.  
 \*3 Long edge feed   
 \*4 Short edge feed   
 \*5 There are six types of fooscap: 8-1/2" x 13-1/2"  220 mm x 330 mm  8-1/2" x 13"  8-1/4" x 13"  8-1/8" x 13-1/4"  and 8" x 13" . Any one of these sizes is selectable. For details, contact your service representative.  
 \*6 Wrinkles or printing errors may occur due to the type, storage or environment that exists when envelope printing is carried out.  
 \*7 Printing on banner paper can only be performed from a PC.  
 \*8 May vary depending on the operating environment and usage.  
 \*9 A4 long edge feed full size/using the first tray/scanning from the original glass surface.  
 \*10 With options installed.  
 \*11 Dimensions when the Paper Trays are pulled out and the Tray Extension of the Bypass Tray is opened.

## Printer Specifications

Type		Embedded
CPU		MB86S72 (1.6GHz)
Memory		4 GB
Print Speed		Same as Copy Speed (when using the same original)
HDD		250GB
Print Resolution		1,800 dpi (equivalent) x 600 dpi (at smoothing) or 1,200 dpi x 1,200 dpi (in 1,200 dpi mode)**
PDL		PCL5e/c Emulation, PCL6 (XL ver. 3.0) Emulation, PostScript 3 Emulation (3016), XPS (Ver. 1.0)
Protocol Support OS	PCL	Windows Vista** / 7** / 8.1** / 10** Windows 2008** / 2008 R2 / Server 2012 / Server 2012 R2
	PS	Windows Vista** / 7** / 8.1** / 10** Windows 2008** / 2008 R2 / Server 2012 / Server 2012 R2 Mac OS X 10.7 / X 10.8 / X 10.9 / X 10.10 / X 10.11(Intel) Linux
	XPS	Windows Vista** / 7** / 8.1** / 10** Windows 2008** / 2008 R2 / Server 2012 / Server 2012 R2
Fonts	PCL	European 80 fonts
	PS	European 137 fonts
Interface		Ethernet (1000BaseT/ 100BaseTX/ 10BaseT), USB 2.0 / 1.1

- \*1 Output speed will be reduced.  
 \*2 Supports the 32bit (x86) or 64bit (x64) environment.

## Scanning Function Specifications

Type		Full-Colour Scanner
Interface		Ethernet (10BASE-T/100BASE-TX/1000BASE-T)
Driver		TWAIN Driver, HDD TWAIN Driver
Protocol		TCP/IP (FTP, SMB, SMTP, WebDAV) (IPv4/IPv6)
Scanning Speed *1	Simplex	120 opm
	Duplex	240 opm
(Colour/B&W)		240 opm
Scanning Size		Max. A3 (11" x 17")
Output Format		TIFF, JPEG, PDF, Compact PDF, XPS, Compact XPS, OOXML (pptx, xlsx**, docx**), Searchable PDF** <sup>2</sup> , PDF/A** <sup>2</sup> , Linearised PDF** <sup>2</sup>
Scanning Resolution	Push	200 dpi / 300 dpi / 400 dpi / 600 dpi
	Pull	100 dpi / 200 dpi / 300 dpi / 400 dpi / 600 dpi
Main Functions		Scan to e-mail, Scan to FTP, Scan to BOX (HDD), Scan to PC (SMB), Network TWAIN, Scan to WebDAV, Scan to Me, Scan to Home, Scan to USB, Scan to Scan Server, Scan to Web Service (WSD-Scan), Device Profile for Web Services (DPWS)
Other Functions		Multi-Method Send, Authentication at the time of e-mail send (SMTP authentication, POP before SMTP), S/MIME, Annotation
Supported operating systems*3		Windows Vista / 7 / 8.1 / 10

- \*1 Speed when scanning A4 original in 300 dpi or less by using the ADF.  
 \*2 Optional  
 \*3 Supports the 32bit (x86) or 64bit (x64) environment.



## Dual Scan Document Feeder

Type		Dual Scan Document Feeder
Supported Paper Size		Max. A3 (Fax mode: Max. 1,000 mm)
Mixed Size		Support
Original Set		Centre guide
Support Paper Weight		Thin paper: 35 to 49 g/m <sup>2</sup> (Simplex) Plain paper: 50 to 210 g/m <sup>2</sup> (Simplex/Duplex), 50 to 128 g/m <sup>2</sup> (Mixed Original)
Paper Capacity		Max. 300 sheets (80 g/m <sup>2</sup> )
Productivity*1	Simplex	Colour/B&W: 120 opm
	Duplex	Colour/B&W: 240 opm
Power Requirements		Supplied from the MFP main body
Dimensions [W] x [D] x [H]		618 x 575 x 180 mm (24-5/16" x 22-5/8" x 7-1/16")
Weight		Approx. 15.1 kg (33-5/16 lb)

- \*1 When copying A4, resolution 600 dpi.

## Internet Fax

Protocol		SMTP, POP
Connection Mode		Full-Mode
Sending Paper Size		A3, B4, A4
Recording Paper Size		Max. A3
Resolution		200 x 100 dpi, 200 x 200 dpi, 400 x 400 dpi, 600 x 600 dpi
Interface		Ethernet (10BASE-T/100BASE-TX/1000BASE-T)
Colour		Support Colour Internet Fax
Format		Send: TIFF-F, Receive: TIFF-F Colour/Grey Scale: TIFF (RFC3949 Profile-C)

## Fax Kit FK-516 (Optional)

Communication		Super G3
Compatible Lines		Public Switch Telephone Network, Private Branch Exchange, Fax Communication Line
Line Density		G3 (8 dot/mm x 3.85 line/mm, 600 x 600 dpi)
Modem Speed		2.4 to 33.6 kbps
Compression		MH/MR/MRR/JBIG
Sending Paper Size		Max. A3 (Long Length Support: Max. 1,000 mm)
Recording Paper Size		Max. A3 (Long Length Max. 1,000 mm – following the page division –)
Transmission Speed		Less than 3 sec. (A4, V.34, 33.6 kbps, JBIG)
Memory		Shared with the copier
Number of Abbr. Dials		2,000
Number of Program Dials		400
Number of Group Dials		100
Sequential Multiple Station Transmission		Max. 600



## Large Capacity Unit LU-303 (Optional)

Support Paper Type (Weight)*		Thin paper (52 to 59 g/m <sup>2</sup> ), Plain paper (60 to 90 g/m <sup>2</sup> ), Thick paper (91 to 256 g/m <sup>2</sup> )
Support Paper Size		A4** <sup>1</sup> , 8-1/2" x 11" ** <sup>1</sup>
Paper Capacity		Plain paper: 3,000 sheets (80 g/m <sup>2</sup> )/3,300 sheets (60 g/m <sup>2</sup> ) Thick paper 1: 2,500 sheets, Thick paper 1+: 1,750 sheets, Thick paper 2: 1,550 sheets, Thick paper 3: 1,300 sheets
Power Requirements		Supplied from the MFP main body
Max. Power Consumption		40 W or less
Dimensions [W] x [D] x [H]		367 x 528 x 405 mm (14-7/16" x 20-13/16" x 15-15/16")
Weight		Approx. 18 kg (39-11/16 lb)

- \*1 Long edge feed   
 \* Thick paper 1: 91 to 120 g/m<sup>2</sup>, Thick paper 1+: 121 to 157 g/m<sup>2</sup>, Thick paper 2: 158 to 209 g/m<sup>2</sup>, Thick paper 3: 210 to 256 g/m<sup>2</sup>



## Large Capacity Unit LU-205 (Optional)

Support Paper Type (Weight)*		Thin paper (52 to 59 g/m <sup>2</sup> ), Plain paper (60 to 90 g/m <sup>2</sup> ), Thick paper (91 to 256 g/m <sup>2</sup> )
Support Paper Size		SRA3 to A4, 12" x 18" to 8-1/2" x 11"
Paper Capacity		Plain paper: 2,500 sheets (80 g/m <sup>2</sup> )/2,750 sheets (60 g/m <sup>2</sup> ) Thick paper 1: 2,000 sheets, Thick paper 1+: 1,450 sheets, Thick paper 2: 1,250 sheets, Thick paper 3: 1,000 sheets
Power Requirements		Supplied from the MFP main body
Max. Power Consumption		40 W or less
Dimensions [W] x [D] x [H]		629 x 556 x 405 mm (24-3/4" x 21-7/8" x 15-15/16")
Weight		Approx. 25 kg (55-1/8 lb)

- \* Thick paper 1: 91 to 120 g/m<sup>2</sup>, Thick paper 1+: 121 to 157 g/m<sup>2</sup>, Thick paper 2: 158 to 209 g/m<sup>2</sup>, Thick paper 3: 210 to 256 g/m<sup>2</sup>

**Finisher FS-537 (Optional)**



<b>Type</b>		Finisher
<b>Support Paper Type</b>		Thin paper / Plain paper (52 to 90 g/m <sup>2</sup> ), Thick paper (91 to 220 g/m <sup>2</sup> ), Transparency, Envelope, Label sheet, Letterhead paper, Tab paper
<b>Support Paper Size</b>		A3 to A5, B6 <sup>1</sup> , A6 <sup>1</sup> , 11" x 17" to 5-1/2" x 8-1/2", 16K, 8K, Postcard (A6 (4" x 6" Card))
<b>Mode</b>		Sort, Group, Offset Sort, Offset Group, Staple
<b>Stacking capacity</b>	Output Tray 1	200 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 2	3,000 sheets (52 to 90 g/m <sup>2</sup> , A4* <sup>1</sup> or smaller, B5 or larger) 1,500 sheets (52 to 90 g/m <sup>2</sup> , B4 or larger) 500 sheets (52 to 90 g/m <sup>2</sup> , A5 or smaller) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 3 (Relay Unit top surface)	100 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
<b>Staple capacity</b>		100 sheets (Thin paper, Plain paper 52 to 80 g/m <sup>2</sup> ) 30 sheets (Plain paper 81 to 90 g/m <sup>2</sup> ) 35 sheets (Coated paper 81 to 90 g/m <sup>2</sup> ) 2 sheets (Thick paper 91 to 209 g/m <sup>2</sup> Cover sheets only)
<b>Power Requirements</b>		Supplied from the MFP main body
<b>Max. Power Consumption</b>		140 W or less
<b>Dimensions [W] x [D] x [H]</b>		622 x 692 x 1,031 mm (24-1/2" x 27-1/4" x 40-9/16")
<b>Weight</b>		Approx. 47 kg (103-5/8 lb)

\*1 Short edge feed

**Finisher FS-537SD (Optional)**



<b>Type</b>		Finisher
<b>Support Paper Type</b>		Thin paper / Plain paper (52 to 90 g/m <sup>2</sup> ), Thick paper (91 to 220 g/m <sup>2</sup> ), Transparency, Envelope, Label sheet, Letterhead paper, Tab paper <b>Centre Staple:</b> 52 to 90 g/m <sup>2</sup> <b>Half-Fold:</b> 52 to 209 g/m <sup>2</sup> (more than 91 g/m <sup>2</sup> Thick paper can be used only as a cover page) <b>Tri-Fold:</b> 52 to 90 g/m <sup>2</sup>
<b>Support Paper Size</b>		A3 to A5, B6 <sup>1</sup> , A6 <sup>1</sup> , 11" x 17" to 5-1/2" x 8-1/2", 16K, 8K, Postcard (A6 (4" x 6" Card)) <b>Centre Staple, Half-Fold:</b> SRA3, A3, B4, A4 <sup>1</sup> , 11" x 17", 8-1/2" x 14", 8-1/2" x 11" <sup>1</sup> , 8K <b>Tri-Fold:</b> A4 <sup>1</sup> , 8-1/2" x 11" <sup>1</sup> , 16K <sup>1</sup>
<b>Mode</b>		Sort, Group, Offset Sort, Offset Group, Staple
<b>Staple capacity</b>		100 sheets (Thin paper, Plain paper 52 to 80 g/m <sup>2</sup> ) 30 sheets (Plain paper 81 to 90 g/m <sup>2</sup> ) 35 sheets (Coated paper 81 to 90 g/m <sup>2</sup> ) 2 sheets (Thick paper 91 to 209 g/m <sup>2</sup> Cover sheets only)
<b>Maximum Number of Sheets that can be Centrestapled</b>		20 (52 to 90 g/m <sup>2</sup> ) sheets, or 19 (90 g/m <sup>2</sup> ) sheets + Thick (209 g/m <sup>2</sup> ) 1 sheet
<b>Maximum Number of Folded Sheets</b>		<b>Half-Fold:</b> 5 sheets or Thick (91 to 209 g/m <sup>2</sup> ) 1 sheet, <b>Tri-Fold:</b> 3 sheets
<b>Stacking capacity</b>	Output Tray 1	200 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 2	2,500 sheets (52 to 90 g/m <sup>2</sup> , A4* <sup>1</sup> or smaller, B5 or larger) 1,500 sheets (52 to 90 g/m <sup>2</sup> , B4 or larger) 500 sheets (52 to 90 g/m <sup>2</sup> , A5 or smaller) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 3 (Relay Unit top surface) Folding output tray	100 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper) 1 to 5 sheets: 35 sets 6 to 10 sheets: 30 sets 11 to 20 sheets: 10 sets <b>Half-Fold (1 to 5 sheet):</b> 35 sets <b>Tri-Fold (1 sheet):</b> 50 sets, (2 sheet): 40 sets, (3 sheet): 30 sets
<b>Power Requirements</b>		Supplied from the MFP main body
<b>Max. Power Consumption</b>		140 W or less
<b>Dimensions [W] x [D] x [H]</b>		622 x 692 x 1,031 mm (24-1/2" x 27-1/4" x 40-9/16")
<b>Weight</b>		Approx. 73 kg (160-15/16 lb)

\*1 Short edge feed

**Post Inserter PI-507 (Optional)**



<b>Applicable</b>		Finisher FS-537/FS-537SD
<b>Support Paper Type (Weight)</b>		Plain paper (60 to 90 g/m <sup>2</sup> ) Thick paper (91 to 209 g/m <sup>2</sup> )
<b>Support Paper Size</b>	Upper Tray	A4, B5, A5* <sup>1</sup> 8-1/2" x 11", 7-1/4" x 10-1/2"* <sup>2</sup> , 5-1/2" x 8-1/2", 16K
	Lower Tray	SRA3, A3 to A5* <sup>1</sup> 12-1/4" x 18" (A3 wide (311.1 x 457.2mm)), 11" x 17" to 5-1/2" x 8-1/2"* <sup>1</sup> , 16K, 8K
<b>Paper Capacity</b>		200 sheets (Plain paper, 80 g/m <sup>2</sup> )
<b>Power Requirements</b>		Supplied from Finisher FS-537/FS-537SD
<b>Dimensions [W] x [D] x [H]</b>		513 x 635 x 222 mm (20-3/16" x 25" x 8-3/4")
<b>Weight</b>		Approx. 12 kg (26-7/16 lb)

\*1 Long edge feed

\*2 Short edge feed

**Job Separator JS-602 (Optional)**



<b>Applicable</b>		Finisher FS-537/FS-537SD
<b>Support Paper Type (Weight)</b>		Plain paper (60 to 90 g/m <sup>2</sup> )
<b>Support Paper Size</b>		A3 to B5, A4* <sup>1</sup> , A5* <sup>1</sup> 11" x 17" to 7-1/4" x 10-1/2", 5-1/2" x 8-1/2"* <sup>1</sup> , 8" x 13", 16K, 8K
<b>Power Requirements</b>		Supplied from Finisher FS-537/FS-537SD
<b>Max. Power Consumption</b>		5 W or less
<b>Dimensions [W] x [D] x [H]</b>		341 x 537 x 149 mm (13-7/16" x 21-1/8" x 5-7/8")
<b>Weight</b>		Approx. 1.75 kg (3-7/8 lb)

\*1 Short edge feed

**Z Folding Unit ZU-609 (Optional)**



<b>Applicable</b>		Finisher FS-537/FS-537SD
<b>Paper Type</b>		Thin paper, Plain paper
<b>Paper Size</b>		A3, B4, 11" x 17", 8-1/2" x 14", 8K
<b>Paper Weight</b>		52 to 90 g/m <sup>2</sup>
<b>Power Requirements</b>		Supplied from Finisher FS-537/FS-537SD
<b>Dimensions [W] x [D] x [H]</b>		101 x 506 x 186 mm (4" x 19-15/16" x 7-5/16")
<b>Weight</b>		Approx. 4.5 kg (9-15/16 lb)

**Punch Kit PK-523 (Optional)**



<b>Applicable</b>		Finisher FS-537/FS-537SD
<b>Number of holes</b>		2 holes, 3 holes, 4 holes
<b>Support Paper Type (Weight)</b>		Thin paper (52 to 59 g/m <sup>2</sup> ), Plain paper (60 to 90 g/m <sup>2</sup> ), Thick paper (91 to 300 g/m <sup>2</sup> )
<b>Support Paper Size</b>		A3 to A5, 11" x 17" to 5-1/2" x 8-1/2", 8" x 13", 16K, 8K
<b>Power Requirements</b>		Supplied from Finisher FS-537/FS-537SD
<b>Dimensions [W] x [D] x [H]</b>		147 x 639 x 234 mm (5-13/16" x 25-3/16" x 9-3/16")
<b>Weight</b>		Approx. 4.5 kg (9-15/16 lb)

**Finisher FS-536 (Optional)**



<b>Type</b>		Finisher
<b>Support Paper Type</b>		Thin paper / Plain paper (52 to 90 g/m <sup>2</sup> ), Thick paper (91 to 220 g/m <sup>2</sup> ), Transparency, Envelope, Label sheet, Letterhead paper, Tab paper
<b>Support Paper Size</b>		A3 to A5, B6 <sup>1</sup> , A6 <sup>1</sup> , 11" x 17" to 5-1/2" x 8-1/2", 16K, 8K, Postcard (A6 (4" x 6" Card))
<b>Mode</b>		Sort, Group, Offset Sort, Offset Group, Staple
<b>Stacking capacity</b>	Output Tray 1	200 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 2	3,000 sheets (52 to 90 g/m <sup>2</sup> , A4* <sup>1</sup> or smaller, B5 or larger) 1,500 sheets (52 to 90 g/m <sup>2</sup> , B4 or larger) 500 sheets (52 to 90 g/m <sup>2</sup> , A5 or smaller) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 3 (Relay Unit top surface)	100 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
<b>Staple capacity</b>		50 sheets (Thin paper, Plain paper 52 to 90 g/m <sup>2</sup> ) 30 sheets (Thick paper 91 to 120 g/m <sup>2</sup> ) 15 sheets (Coated paper 121 to 209 g/m <sup>2</sup> )
<b>Power Requirements</b>		Supplied from the MFP main body
<b>Max. Power Consumption</b>		105 W or less
<b>Dimensions [W] x [D] x [H]</b>		528 x 641 x 1,023 mm (20-5/8" x 25-1/4" x 40-1/4")
<b>Weight</b>		Approx. 36 kg (79-3/8 lb)

\*1 Short edge feed

**Finisher FS-536SD (Optional)**



<b>Type</b>		Finisher
<b>Support Paper Type</b>		Thin paper / Plain paper (52 to 90 g/m <sup>2</sup> ), Thick paper (91 to 220 g/m <sup>2</sup> ), Transparency, Envelope, Label sheet, Letterhead paper, Tab paper <b>Centre Staple:</b> 52 to 90 g/m <sup>2</sup> <b>Half-Fold:</b> 52 to 90 g/m <sup>2</sup> (more than 91 g/m <sup>2</sup> Thick paper can be used only as a cover page) <b>Tri-Fold:</b> 52 to 90 g/m <sup>2</sup>
<b>Support Paper Size</b>		A3 to A5, B6 <sup>1</sup> , A6 <sup>1</sup> , 11" x 17" to 5-1/2" x 8-1/2", 16K, 8K, Postcard (A6 (4" x 6" Card)) <b>Centre Staple, Half-Fold:</b> SRA3, A3, B4, A4 <sup>1</sup> , 11" x 17", 8-1/2" x 14", 8-1/2" x 11" <sup>1</sup> , 8K <b>Tri-Fold:</b> A4 <sup>1</sup> , 8-1/2" x 11" <sup>1</sup> , 16K <sup>1</sup>
<b>Mode</b>		Sort, Group, Offset Sort, Offset Group, Staple
<b>Staple capacity</b>		50 sheets (Thin paper, Plain paper 52 to 90 g/m <sup>2</sup> ) 30 sheets (Thick paper 91 to 120 g/m <sup>2</sup> ) 15 sheets (Coated paper 121 to 209 g/m <sup>2</sup> )
<b>Maximum Number of Sheets that can be Centrestapled</b>		20 (52 to 90 g/m <sup>2</sup> ) sheets, or 19 (90 g/m <sup>2</sup> ) sheets + Thick (209 g/m <sup>2</sup> ) 1 sheet
<b>Maximum Number of Folded Sheets</b>		<b>Half-Fold:</b> 5 sheets or Thick (91 to 209 g/m <sup>2</sup> ) 1 sheet, <b>Tri-Fold:</b> 3 sheets
<b>Stacking capacity</b>	Output Tray 1	200 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 2	2,000 sheets (52 to 90 g/m <sup>2</sup> , A4* <sup>1</sup> or smaller, B5 or larger) 1,500 sheets (52 to 90 g/m <sup>2</sup> , B4 or larger) 500 sheets (52 to 90 g/m <sup>2</sup> , A5 or smaller) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper)
	Output Tray 3 (Relay Unit top surface) Folding output tray	100 sheets (52 to 90 g/m <sup>2</sup> ) 20 sheets (91 to 220 g/m <sup>2</sup> , special paper) 1 to 3 sheets: 20 sets 4 to 10 sheets: 10 sets 11 to 20 sheets: 5 sets <b>Tri-Fold (1 sheet):</b> 30 sets <b>Tri-Fold (2 to 3 sheets):</b> 10 sets
<b>Power Requirements</b>		Supplied from the MFP main body
<b>Max. Power Consumption</b>		140 W or less
<b>Dimensions [W] x [D] x [H]</b>		528 x 641 x 1,023 mm (20-5/8" x 25-1/4" x 40-1/4")
<b>Weight</b>		Approx. 60 kg (132-5/16 lb)

\*1 Short edge feed

**Punch Kit PK-520 (Optional)**



<b>Applicable</b>		Finisher FS-536/FS-536SD
<b>Number of holes</b>		2 holes, 3 holes, 4 holes
<b>Support Paper Type (Weight)</b>		Thin paper (52 to 59 g/m <sup>2</sup> ), Plain paper (60 to 90 g/m <sup>2</sup> ), Thick paper (91 to 300 g/m <sup>2</sup> )
<b>Support Paper Size</b>		A3 to A5, 11" x 17" to 7-1/4" x 10-1/2", 16K, 8K
<b>Power Requirements</b>		Supplied from Finisher FS-536/FS-536SD
<b>Dimensions [W] x [D] x [H]</b>		61 x 492 x 142 mm (2-3/8" x 19-3/8" x 5-9/16")
<b>Weight</b>		Approx. 1.8 kg (3-15/16 lb)